

Part Number: 1400

SAFETY DATA SHEET (SDS)

Revision Date: 1/20/2025 Version 1.5

1. PRODUCT AND COMPANY IDENTIFICATION

1.1	Product Name: Part Number: CAS-No.: SDS Number:	Sudan IV Stain, Herxheimer Alcoholic 1400 Not applicable 4440	
1.2	Recommended Use:	Laboratory Chemicals	
1.3	Company: Telephone: Fax: Website: Email:	NEWCOMER SUPPLY 1020 PRAIRIE VIEW CT WAUNAKEE WI 53597-8512 1-800-383-7799 1-608-831-0866 <u>www.newcomersupply.com</u> info@newcomersupply.com	24 HOUR EMERGENCY CONTACT CALL CHEMTREC: 1-800-424-9300 Contact CHEMTREC only in the event of an emergency involving a chemical spill, leak, fire, exposure or other accident.

2. HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification, (in accordance with 29 CFR1910.1200) Flammable liquid, Category 2 Serious Eye Damage/Eye irritation, Category 2A Carcinogenicity, Category 2 Acute toxicity (oral), Category 4 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4 Specific Target Organ Toxicity – Single exposure, Category 3

2.2 GHS Label elements Signal Word

DANGER

Pictogram



Hazard Statement(s):

- · Highly flammable liquid and vapour
- · Causes serious eye irritation
- · Suspected of causing cancer
- · Harmful if swallowed
- · Harmful in contact with skin
- · Harmful if inhaled
- May cause respiratory irritation
- · May cause drowsiness or dizziness

Precautionary Statement(s):

Prevention:

- \cdot Obtain special instructions before use.
- · Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces No smoking.
- · Keep container tightly closed.
- · Ground/bond container and receiving equipment.
- · Use explosion-proof fume hood/electrical/ventilating/light equipment.
- · Use only non-sparking tools.
- · Take precautionary measures against static discharge.
- · Wear protective gloves/protective clothing/eye protection/face protection.
- \cdot Wash skin thoroughly after handling.
- \cdot Do not eat, drink or smoke when using this product.
- · Avoid breathing dust/fume/gas/mist/vapours/spray.

ͶϴϢϲϘϺϴΓʹͽϓϷϘͰϒ·

SAFETY DATA SHEET (SDS)

Revision Date: 1/20/2025

Version 1.5

Part Number: 1400

 \cdot Use only outdoors or in a well-ventilated area.

Response:

- In case of fire use carbon dioxide, dry chemical or alcohol-resistant foam.
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with
- . water/shower.
- \cdot Wash contaminated clothing before reuse.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy
- . to do – continue rinsing.
- · If eye irritation persists get medical advice/attention.
- · IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- · Rinse mouth.
- · Specific treatment: see first aid measures in section 4.
- \cdot IF exposed or concerned: Get medical advice/attention.
- Storage:
- \cdot Store in a well ventilated place. Keep cool.
- Keep container tightly closed.
- · Store locked up.
- Disposal:
- · Dispose of contents/ container to an approved waste disposal plant.
- 2.3 Description of any hazards not otherwise classified None
- 2.4 >1% of mixture with unknown acute toxicity None

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixture

Hazardous Components

Compone	nt	Concentration		
Name	Ethyl Alcohol			
CAS-No.	64-17-5	43-44%		
Name	Isopropyl Alcohol			
CAS-No.	67-63-0	7-8%		
Name	Methyl Alcohol			
CAS-No.	67-56-1	2-3%		
Name	Methyl Isobutyl Ketone			
CAS-No.	108-10-1	<1%		
Name	Acetone	÷		
CAS-No.	67-64-1	50%		

4. FIRST-AID MEASURES

4.1 Description of necessary measures

Inhalation (breathing)

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention.

Skin Contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF exposed or concerned: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.



Revision Date: 1/20/2025

Version 1.5

Part Number: 1400

Ingestion (swallowed)

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.

- **4.2** Most important symptoms and or effects, acute and delayed The most important symptoms/effects are presented in Section 2 and or Section 11.
- **4.3** Indication of any immediate medical attention and special treatment needed No data available

5. FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media

Carbon dioxide, dry chemical, water spray, alcohol-resistant foam.

5.2 Specific hazards arising from the substance or mixture No data available

5.3 Protective equipment and precautions for fire-fighters

Wear a positive-pressure self-contained breathing apparatus if necessary. Wear chemical resistant clothing as recommended by clothing manufacturer.

NFPA Rating			
Health	Fire	Reactivity	
hazard:	2 hazard:	3 hazard:	0

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Apply personal protective equipment (see Section 8.2). Use in a properly ventilated area. Avoid breathing vapors. Avoid skin contact. Avoid eye contact. Wash hands after use. In case of large spill, remove personnel to a safe area. Keep product away from heat, flame, ignition sources, and reactive materials. Avoid accumulation of vapor to form explosive concentration. Pay particular attention to low areas where vapor accumulates more easily.

6.2 Methods and material for containment and cleaning up

Apply personal protective equipment (see Section 8.2). Contain spill. Prevent further leakage if possible and safe to do so. Ensure proper ventilation. For small amounts, wipe or absorb spill using inert material and dispose of according to local regulations. For large amounts, evacuate area and limit access. Prevent entry of material into sewage drains and confined areas. Dispose of any contaminated materials according to local regulations. Eliminate sources of ignition.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces – No smoking. Do not breathe dust/fume/gas/mist/vapours/spray.Wear protective gloves/protective clothing/eye protection/face protection.

7.2 Conditions for safe storage, including any incompatibilities

Refer to Section 2.2 for proper storage temperature. Store the tightly closed container in a cool, dry, well-ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters

Components with limit values that require monitoring at the workplace

		Regulatory	· · ·	Parameters
Ethyl Alcohol	64-17-5	OSHA PEL	TWA	1000 ppm (1900 mg/m ³)



Revision Date: 1/20/2025

Version 1.5

Part	Number:	1400

		-		
		ACGIH TLV	TWA	1000 ppm (1880 mg/m ³)
		NIOSH REL	TWA	1000 ppm (1900 mg/m ³)
Component	CAS-No.	Regulatory	Value	Parameters
Methyl Alcohol	67-56-1	OSHA PEL	TWA	200 ppm (980 mg/m ³)
		ACGIH TLV	STEL	200 ppm (1,230 mg/m ³)
		ACGIH TLV	STEL	50 ppm (1,230 mg/m ³)
		NIOSH REL	TWA	200 ppm (980 mg/m ³)
		NIOSH REL	STEL	250 ppm (980 mg/m ³)
Component	CAS-No.	Regulatory	Value	Parameters
Isopropyl Alcohol	67-63-0	OSHA PEL	TWA	400 ppm (980 mg/m ³)
		ACGIH TLV	TWA	400 ppm (983 mg/m ³)
		ACGIH TLV	STEL	500 ppm (1,230 mg/m ³)
		NIOSH REL	TWA	400 ppm (980 mg/m ³)
		NIOSH REL	STEL	500 ppm (980 mg/m ³)
Component	CAS-No.	Regulatory	Value	Parameters
Methyl Isobutyl				2
Ketone	108-10-1	OSHA PEL	TWA	100 ppm (410 mg/m ³)
		ACGIH TLV	TWA	50 ppm (205 mg/m ³)
		ACGIH TLV	STEL	75 ppm (307 mg/m ³)
		NIOSH REL	TWA	50 ppm (205 mg/m ³)
		NIOSH REL	STEL	75 ppm (300 mg/m ³)
Component	CAS-No.	Regulatory	Value	Parameters
Acetone	67-64-1	OSHA PEL	TWA	1,000 ppm (2,400 mg/m ³)
		ACGIH TLV	TWA	750 ppm (1,780 mg/m ³)
		ACGIH TLV	STEL	1,000 ppm (2,380 mg/m ³)
		NIOSH REL	TWA	250 ppm (590 mg/m ³)

8.2 Exposure Controls

Appropriate engineering controls

Use in a properly ventilated area. Remove/wash before reuse contaminated clothing. Wash hands upon exiting work premises. Use product in an appropriately designated fume hood. Take measures to keep concentrations below acceptable limits.

8.3 Personal Protective Equipment

Eye/Face protection

Wear chemical safety goggles and/or a full face shield if splashing is possible. Keep eye wash fountain nearby.

Skin Protection

Wear chemical-resistant gloves. Gloves should be resistant to components of product. Refer to glove manufacturer for appropriate type and glove thickness.

Body Protection

No data available

Respiratory Protection



Part Number: 1400

Revision Date: 1/20/2025 Version 1.5

Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134). In case of emergency, entry into or escape from unknown concentrations select the highest level approved respiratory protection available.

Other Information None

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state	Colorless liquid
Odor	Alcoholic odor
Odor threshold	No data available
рН	No data available
Melting point/freezing point	No data available
Initial boiling point and boiling range	No data available
Flash point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper flammability or explosive limits	No data available
Lower flammability or explosive limits	No data available
Vapor pressure	No data available
Vapor density	No data available
Relative density	No data available
Solubility(ies)	Miscible with water and many organic liquids
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity No data available

10.2 Chemical stability

Stable in a closed container within label-specified storage temperature and expiration date.

- **10.3** Possibility of hazardous reactions No data available
- **10.4** Conditions to avoid Heat, sparks, open flame, and ignition sources.

10.5 Incompatible materials

Strong oxidizers, potassium dioxide, bromine pentafluoride, acetyl bromide, acetyl chloride, platinum, sodium concentrated sulfuric acid, potassium and hydrogen peroxides, platinum black, calcium hypochlorite, silver oxide, ammonia, nitric acid, mercuric nitrate, silver nitrate, magnesium perchlorate, isocyanates, mineral acids, and chloroform. Permanganates, chlorates, nitrates, chlorine, bromine, and fluorine. Acetic Acid and nitric acid.

10.6 Hazardous decomposition products No data available

11. TOXICOLOGICAL INFORMATION



Revision Date: 1/20/2025

Version 1.5

Part Number: 1400

11.1 Information on toxicological effects

Inhalation exposure

Inhaling ethyl alcohol, methyl alcohol, isopropyl alcohol, and acetone can irritate the nose, throat and lungs causing coughing and/or shortness of breath. Breathing methyl isobutyl ketone can irritate the nose and throat causing coughing and wheezing. Breathing methyl isobutyl ketone vapor can cause headache, loss of appetite, nausea, vomiting, and diarrhea. Exposure to high concentrations of acetone can cause headache, nausea and vomiting, dizziness, lightheadedness and even passing out. Acetone: Headache, lightheadedness, nasal irritation weres noted in workers exposed to concentrations considerably in excess of 1,000 ppm and perhaps as high as 6,500 ppm. Exposure to high concentrations of use headache, nausea and vomiting, dizziness, lightheadedness and even passing out.

Oral exposure

Oral exposure to ethyl alcohol, methyl alcohol, and isopropyl alcohol can cause headache, drowsiness, nausea and vomiting, and unconsciousness. It can also affect concentration and vision. Acetone exposure can irritate the throat.

Dermal exposure

Contact with ethyl alcohol can irritate the skin.

Skin corrosion/irritation

Prolonged or repeated exposure to ethyl alcohol and acetone can cause drying and cracking of the skin with peeling, redness and itching.

Serious eye damage/irritation

Contact with ethyl alcohol can irritate and burn the eyes. Acetone has been reported to cause burning sensation in the eyes at vapor concentration of 500 ppm. Reports of irritation in acclimated workers include a range of 1000-1500 ppm.

Respiratory or skin sensitization

No data available

Germ Cell mutagenicity No data available

Reproductive toxicity

Repeated oral exposure to ethyl alcohol may cause spontaneous abortions, as well as birth defects and other developmental problems. This condition is referred to as "fetal alcohol syndrome." There is limited evidence that oral exposure to ethyl alcohol may decrease fertility in males.

Specific target organ toxicity - single exposure

Acetone and ethyl alcohol exposure may affect the kidneys, liver, and nervous system.

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Acute toxicity

www.newcomersupply.com



Part Number: 1400

Revision Date: 1/20/2025 Version 1.5

Ethyl Alcohol: LD50 rat oral 3450 mg/kg LD50 mouse oral 7060 mg/kg LC50 rat inhalation 20000 ppm/10H LC50 mouse inhalation 20363 ppm/4H Acetone: LD50 rat oral 5800 mg/kg LD50 rabbit oral 5340 mg/kg LD50 mouse oral 3000 mg/kg LCL0 mouse inhalation 45,455 ppm/1H

Carcinogencity

IARC: Methyl Isobutyl Ketone: Group 2B Possible human carcinogen NTP: None of the components are listed OSHA: None of the components are listed

Additional information

RTECS: No data available

12. ECOLOGICAL INFORMATION

- **12.1 Ecotoxicity** No data available
- **12.2** Persistence and degradability No data available
- **12.3 Bioaccumulative potential** No data available
- 12.4 Mobility in soil No data available
- **12.5** Other adverse effects No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste disposal methods Contents

Dispose of contents in a safe manner to comply with local, state and federal regulations. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of packaging in a safe manner to comply with local, state and federal regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. TRANSPORT INFORMATION

14.1 DOT (US)

UN-Number
Proper shipping name
Hazard class
Packing group
Environmental hazards

No data available No data available No data available No data available No data available

15. REGULATORY INFORMATION



Part Number: 1400

Revision Date: 1/20/2025 Version 1.5

16. OTHER INFORMATION

Preparation Information Newcomer Supply Inc. 800-383-7799 www.newcomersupply.com Copyright © Newcomer Supply Inc. All rights reserved.