

# SAFETY DATA SHEET

Daido Sangyo Co.,Ltd.  
NC Bldg., 3-48-2 Minami-Otsuka,  
Toshima-ku, Tokyo 170-0005, Japan  
Tel +81(3)3984-0384 / Fax +81(3)3984-0453

REVISED 9th June, 2015

## Section 1 - Identification of the preparation and company

Trade name: Mount Quick Tube  
Manufacturer: Daido Sangyo Co., Ltd.  
Emergency tel: +81 3 3984 0384  
Product code: Mount Quick Tube  
Use of substance / prepareate :  
Mounting medium for glass slide

## Section 2 - Hazards identification

Hazardous health and Acute Toxicity or Chronic Toxicity:

\* This product contains industrial chemicals, avoid skin contact

## Section 3 - Composition / information on ingredients

Xylene 60.0% CAS# 1330-20-7



Acrylic resin emulsion adhesive 40.0% CAS# 64742-95-6



#### Section 4 - First-aid measures

\* Skin contact:

In case of being contacted the skin, wash thoroughly with soap and water, liquid extremely.

\* Eye contact:

Irritating to eye, flush with plenty of water - call a physician.

\* If swallowed and emergency procedure

Vomits and seek medical help.

\* Antidote

#### Section 5 – Fire-fighting measures

Suitable extinguishing media:

- \* Ordinary chemical extinguisher, PVA 10% aqueous solution or 10% gum arabic aqueous solution

Extinguish Method

- \* Fire extinguisher

#### Section 6 - Accidental release measures

Protect hand with glove and wipe it off with a waste.

Collect in the container which can be sealed.

#### Section 7 - Handling and storage

Handling:

- \* Keep away from heat and open flame and small children directions.
- \* In case of skin contact flush with plenty of water.

Storage:

Keep from heat and open flame, strong oxidants and small children.

Storage temperature:

25°C

#### Section 8 - Exposure controls / personal protection

Use in a well-ventilated place and keep from heat and open flame.

#### Section 9 - Physical and chemical properties

|                              |           |
|------------------------------|-----------|
| physical state:              | liquid    |
| appearance:                  | colorless |
| solubility in water(at20°C): | 5%        |
| boiling point:               | 130°C     |
| viscosity(at 20°C):          | 33 cps    |
| specific gravity:            | 0.89sp    |
| vapour pressure(at 20°C):    | 20 mmHg   |
| vapour Density(air-1):       | 0.95      |

#### Section 10 - Stability and reactivity

Conditions / substances to avoid:

Stable under normal conditions.

Use in well ventilated area and keep from heat and open flame.

#### Section 11 - Toxicological information

Not available

#### Section 12 - Ecological information

Not available

#### Section 13 - Disposal considerations

Observe all state and local environmental regulations regarding waste disposal.

#### Section 14 - Transport information

UN number, hazard class, packing group

\* Xylene 1307, 3, II

\* Acrylic resin emulsion adhesive none, 3, II

**Section 15 - Regulatory information**

Depends on the laws and ordinances of each country

**Section 16 - Other information**

not available

---

end of safety data sheet